

3200

Handheld Linear Imager

The 3200 delivers quality linear barcode scanning and user friendly ergonomics, combined in a solution that's affordable and dependable for a wide variety of applications. Whether you're automating a pen and paper process, or require a high-quality yet cost effective barcode scanner to replace your existing devices, the Honeywell 3200 is an ideal solution.

Linear imaging technology provides high scanning performance on all linear barcodes – even those that are damaged or poorly printed - and features the added value of being 100% solid-state, with no moving parts that can fail or become misaligned.

Unlike other value-priced solutions that sacrifice usability features, the 3200 provides an ergonomic pistol-grip and user-preferred finger trigger design for comfortable and intuitive use.

With a 2-year warranty and durable design, the 3200 provides a great value to customers who require reliable barcode scanning solution at an affordable price.



Features

- **Linear Imaging Technology:** Fast barcode scanner, even on poorly printed or damaged linear codes.
- **User-Friendly Design:** Pistol-style with index finger trigger ensuring operator comfort and ease of use.
- **Reliable:** The durability of 100% solid state technology and a 2-year warranty.
- **Ease of Connectivity:** Common interfaces are integrated to ensure fast and easy connection to your host or PC.
- **Future Proof Symbology Support:** GTIN compliant, GS1 DataBar capable.
- **Intuitive Aiming Line:** Thin, crisp aiming line for ease-of-use in scanning bar coded menus and densely populated documents.
- **Intuitive User Feedback:** Fully programmable options for application-specific "good read" LED and beeper settings.

High Performance Linear Image Scanners:



3800g
General Purpose Scanner



3820
Cordless Light Industrial Scanner



3800i
Industrial Scanner

3200 Specifications

Performance

Illumination:	630 NM Visible Red LED
Receiving Device:	2048 element linear imager
Reading Distance:	From .5 in. (1.3 cm) to 10 in. (25 cm) on medium density bar codes
Reading Width:	15 mil code 4 in. (11 cm) wide at 3.5 in. (9 cm)
Resolution:	4 mil. at 4 in. (10 cm) distance
Skew Angle:	±55°
Pitch Angle:	±55°
Minimum Symbol Contrast:	30%
Scan Rate:	200 plus scans per second

Mechanical/Electrical

Length:	3.7 in. (9.5 cm)						
Height:	6.0 in. (15.2 cm)						
Width:	2.7 in. (6.8 cm)						
Weight:	5.1 oz. (143 g)						
Housing:	UL 94V0 grade						
Power Requirements:	3200: 4.75 - 5.25Vdc at scanner						
Current Draw (Maximum):	<table border="1"> <tr> <td>Input</td> <td>Scanning</td> <td>Idle</td> </tr> <tr> <td>5 V</td> <td>235mA</td> <td>86mA</td> </tr> </table>	Input	Scanning	Idle	5 V	235mA	86mA
Input	Scanning	Idle					
5 V	235mA	86mA					

Power Supply

Noise Rejection:	Maximum 100mV peak to peak, 10 to 100 kHz
-------------------------	---

Environmental

Operating Temperature:	+32°F to +122°F (0°C to +50°C)
Storage Temperature:	-4°F to 140°F (-20°C to +60°C)
Humidity:	0 to 95%, non-condensing
Mechanical Shock:	Operational after 25 drops from 4 ft. (1.2 m) to concrete
Ambient Illumination:	0 - 70,000 lux
ESD Protection:	Exceeds CE EN55024
Vibration:	Withstands 5G peak from 22 to 300 Hz
Agency:	USA: FCC Part 15 subpart B Class B. Canada: ICES-003 Class B. Europe: CE 2004/108/EC EMC Directive to EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3. 2006/95/EC Low Voltage Directive Australia/NZ: C-Tick mark Japan: VCCI
MTBF:	per MIL-HDBK-217F Ground Benign exceeds 85,000 hours
Symbologies:	Codabar, Code 3 of 9 including PARAF, Interleaved 2 of 5, Straight 2 of 5 Industrial, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Postal Code, GS1 DataBar. 2005 Sunrise/GTIN compliant
Interfaces:	3200: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, USB, and (Host Powered) TTL level RS-232
Warranty:	Two year factory warranty.

Typical Performance*

Narrow Width	Depth of Field
5.0 mil	1.5 - 4.5 in. (3.8 - 11.4 cm)
13 mil (100% UPC)	.5 - 9 in. (1.3 - 23 cm)

*may be impacted by bar code quality and environmental conditions

Automation and Control Solutions

Honeywell
Imaging and Mobility
Nijverheidsweg 9-13
5627BT Eindhoven, The Netherlands
Tel: +31 (0)40 2901600
eusales@handheld.com
www.honeywell.com/aidc

Dallam Court, Dallam Lane
Warrington, Cheshire WA2 7LT, UK
Tel: +44 (0)1925 240055

Honeywell